



PC250



PC250 - Enclosed cabinet conventional style.

MODEL	PC250
STRAP WIDTH	1/4, 3/8, 1/2, 5/8
COIL SIZE	I.D. WIDTH O.D. 8IN. X 8IN. X 19IN.
TENSION	90 LBS.
DIMENSIONS	W X L X H 42 X 24 X 29
TABLE HEIGHT	31IN.
NET HEIGHT	205 LBS.
POWER SUPPLY	120 VAC SINGLE PHASE

ALL SERIES 200 MODELS FEATURE

1. Same high quality strapping head and controls.
2. “Instant” heat. Approximately 10 second warmup time for sealing system.
3. External tension adjustment.
4. Energy efficient - motor only runs as needed.



6277 HEISLEY ROAD
 MENTOR, OHIO 44060
 (440) 357-1500
 FAX (440) 352-9553
 1-800-548-9557

WEST COAST DISTRIBUTION CENTER
 11920 ALTAMAR PLACE
 SANTA FE SPRINGS, CA 90670
 (562) 903-4576
 FAX (562) 903-4579
 1-800-899-0822



Strapping speed	2.5 sec/strap (60Hz)
Tension	30 - 90 lbs.
Sealing method	heating element
Strap width	5, 6, 9, 12, 15.5mm of P.P. band 1/4", 3/8", 1/2", 5/8"
Reel outside Dia.	19"
Power	AC 110/220, 50/60Hz, 1PH
Power Consumption	0.57KW
Table Height	30 inches
Machine weight	220 lbs.
Layout dimension	291/2"H x 361/4"W x 23"D
Identification	H-height, W-width, D-depth

*Specification subject to change without notice.

Strapping speed	2.5 sec/strap (60Hz)
Tension	30 - 90 lbs.
Sealing method	heating element
Strap width	5, 6, 9, 12, 15.5mm of P.P. band 1/4", 3/8", 1/2", 5/8"
Reel outside Dia.	19"
Power	AC 110/220, 50/60Hz, 1PH
Power Consumption	0.57KW
Table Height	30 inches
Machine weight	185 lbs.
Layout dimension	291/2"H x 361/4"W x 23"D
Identification	H-height, W-width, D-depth

*Specification subject to change without notice.

PC-101



PC-102



**SCOPE OF APPLICATION:
GENERAL PURPOSE
INDUSTRIAL STRAPPING**

ALL SERIES 100 MODELS FEATURE

- CE safety standard design
- Safety switch
- Reliable P.C. Board electric control
- Hinge type table
- Rigid caster with brake
- Reel unit is core size adjustable design for 8", 9" & 11" diameter.