

WULFTEC® STRETCH WRAPPING EQUIPMENT



M. J. MAILLIS

WULFTEC® WE FEAR NO PACKAGING CHALLENGE

M. J. MAILLIS

WULFTEC®

Wulftec International Inc.
209 Wulftec
Ayer's Cliff, Quebec
Canada J0B 1C0

EXCLUSIVE ELEMENTS

NO-THREAD® POWERED PRE-STRETCH CARRIAGE (50-300% PRE-STRETCH RATIO)



- SAFE AND FAST LOADING PROCESS
- LEXAN GATE SAFETY COVER
- DOUBLE LATCH SAFETY GATE LOCK
- VIRTUALLY SILENT OPERATION
- EXCELLENT FILM STRETCHING PERFORMANCE
- MAINTENANCE FREE AC MOTOR WITH VARIABLE FREQUENCY DRIVE FOR CORNER COMPENSATION
- LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND

ALLEN BRADLEY - PLC

- PROGRAMMING FLEXIBILITY
- RELIABLE
- ACCESSIBLE VIA MODEM*
- NON-PROPRIETARY
- EASY TROUBLE SHOOTING



*DEPENDING ON MODEL

ALLEN BRADLEY VARIABLE FREQUENCY DRIVES

- EASY SET-UP
- ACCURATE SPEED CONTROL
- EASY DIGITAL READOUT
- EXCELLENT REPEATABILITY OF SETTINGS
- MAINTENANCE FREE



Wulftec International Inc. guarantees 10 years of trouble-free ring-gear operation with unlimited wrapping cycles.

REMARKABLE STRETCH WRAPPERS



GET THE EXACT STRETCH WRAPPER YOU NEED...
...PAY ONLY FOR THE FEATURES YOU WANT!

THE SMART APPROACH TO SEMI-AUTOMATIC STRETCH WRAPPING

With the SMART™ Series, you get to pick and choose the individual components that will best meet your stretch wrapping needs in four easy steps:


- STEP 1:** Choose your turntable
- STEP 2:** Choose your wrap height
- STEP 3:** Choose your carriage
- STEP 4:** Choose your control panel



The SMART™ machine has been designed to allow you to upgrade the individual components at any time.
Get SMART with the Wulftec SMART™ Series.

WWW.WULFTEC.COM

SMLPA-200
FULLY AUTOMATED
LOW PROFILE TURNTABLE



Up to 50 loads per hour*
Maximum load size:
50"W x 50"L x 80"H
Load weight: 5,000 lbs. capacity
Machine dimensions:
66"W x 119½"L x 86¾"H
12 RPM variable speed
Pull cord to start cycle

WCA-200
CONVEYORIZED FULLY
AUTOMATIC TURNTABLE



Up to 60 loads per hour*
Maximum load size:
48"W x 48"L x 80"H
Load weight: 4,000 lbs. capacity
Machine dimensions:
200"W x 135"L x 102½"H
15 RPM variable speed

WRT-200
SEMI-AUTOMATIC FREE
STANDING ROTARY ARM



Up to 50 loads per hour*
Maximum load size:
56"W x 56"L x 80"H
Load weight: unlimited
Machine dimensions:
130"W x 147¾"L x 117½"H**
12 RPM variable speed

WCRT-200
CONVEYORIZED
AUTOMATIC ROTARY ARM



Up to 100 loads per hour*
Maximum load size:
48"W x 48"L x 80"H
Load weight: 4,000 lbs. capacity
Machine dimensions:
148"W x 138"L x 140"H**
17 RPM variable speed

WRTA-150
NON-CONVEYORIZED
AUTOMATED ROTARY ARM



Up to 50 loads per hour*
Maximum load size:
56"W x 56"L x 80"H
Load weight: unlimited
Machine dimensions:
130"W x 165½"L x 117½"H**
12 RPM variable speed
Pull cord to start cycle

WRWA-200
FULLY AUTOMATIC
HORIZONTAL WRAPPER



Up to 120 loads per hour*
Maximum load size:
maximum diagonal load dimension
must be 8" (4" on each side) shorter
than ring size
Available ring sizes:
36, 60, 90 inch dia.
Load weight: 4,000 lbs. capacity
RPM based on ring size

WCA-150
CONVEYORIZED FULLY
AUTOMATIC TURNTABLE



Up to 50 loads per hour*
Maximum load size:
48"W x 48"L x 76"H
Load weight: 4,000 lbs. capacity
Machine dimensions:
199"W x 135"L x 96"H
12 RPM variable speed

WRING-500
FULLY AUTOMATIC
ROTARY RING WRAPPER



Up to 120 loads per hour*
Maximum load size:
48"W x 50"L x 80"H
(maximum load diagonal 70")
Load weight: 4,000 lbs. capacity
Machine dimensions:
108"W x 145"L x 162"H**
50 RPM variable speed

THE WULFTEC ADVANTAGE:

- > ALLEN BRADLEY PLC FOR MORE FLEXIBILITY
- > AC VARIABLE FREQUENCY DRIVES AND MOTORS
- > HEAVY-DUTY STEEL CONSTRUCTION
- > NO-THREAD® POWERED PRE-STRETCH CARRIAGE
- > SUPERIOR WARRANTIES



- > LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND
- > 10-YEAR WARRANTY ON STRUCTURAL FRAME
- > 10-YEAR WARRANTY ON RING GEAR
- > 3-YEAR UNLIMITED CYCLE WARRANTY

* Production rate based on load size and configuration.
** Overall dimensions of machine in operation.